

Contract Gloss

Leyland Contract Gloss is specially formulated to provide a high gloss finish to wood and metal surfaces. The outstanding opacity, brilliant whiteness and excellent application properties make it ideal for interior and exterior new work application.

Recommended uses

Interior ✓ Exterior ✓

Type of substrate

Wood and metal.

Colour availability

Brilliant White (5ltr & 2.5ltr)

Finish

Gloss

Volume solid

60%

Coverage

Leyland Contract Gloss will cover approximately 17 square metres per litre depending on the nature and porosity of the surface.

Drying time

Recoat after 16-24 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

VOC content

HIGH VOC CONTENT 25-50% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 300 g/l (2010). This product contains max 300 g/l VOC.

Film thickness

Wet: 60µm
Dry: 36µm

Preparation

All surfaces to be painted should be clean, dry and free from grease. Loose, flaking or blistered paint should be completely removed. Prime all new and bare surfaces with the appropriate Leyland Primer followed by Leyland Undercoat. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Application

Stir well before use. Do not thin, except for absorbent surfaces, or when applying by roller or spray when a small quantity of clean water may be added. Suitable for application by brush, roller or spray. Apply paint evenly by brush or roller and avoid overspreading. If required apply a second coat after 2-4 hours. Do not apply in temperatures below 10°C.

Cleaning

Stir well before use. Apply by brush or roller. The brush should be fully loaded for best results. Apply one or more coats as required and allow 16-24 hours between coats under normal conditions.

Warning

- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Safety data sheet available on request.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.

