

Contract Primer Undercoat

A water-based combined primer and undercoat based on a high quality acrylic resin. Specially formulated to provide a low odour, quick drying basecoat to bare timber surfaces, making it ideal for interior and exterior new work application.

Recommended uses

Interior ✓ Exterior ✓

Type of substrate

Wood.

Colour availability

Brilliant White (5ltr & 2.5ltr)

Finish

N/A

Volume solid

30%

Coverage

Leyland Contract Primer Undercoat will cover approximately 13 square metres per litre depending on the nature and porosity of the surface.

Drying time

Recoat after 1-2 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

VOC content

MINIMAL VOC CONTENT 0-0.29% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130 g/l (2010). This product contains max 3 g/l VOC.

Film thickness

Wet: 75µm
Dry: 23µm

Preparation

All surfaces to be painted should be clean, dry and free from grease. Loose, flaking or blistered paint should be completely removed. Prime all new and bare surfaces with the appropriate Leyland Primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Application

Stir well before use. Apply by brush or roller. Apply liberally, brushing firmly into the surface. Treat all accessible timber, in particular the end grain. Do not apply when the temperature is below 10°C or externally when rain is imminent.

Cleaning

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Warning

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.